

Sewing Pattern — Blouse 5904

Recommendations on fabric: silk

You will also need: elastic thread

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: along the edge of the garment 2 cm, on top edge of back, front and sleeve – 4 cm, along lower edge of sleeve — 4 cm, all other seams - 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Sleeve - 2 details
2. Front – 1 detail
3. Back - 1 detail

INSTRUCTIONS:

1. Stitch sleeve on armhole to back and front. Serge and press seam to sleeve.
2. Sew side seams of the blouse, sewing sleeve seams at the same time. Serge seams and press toward back.
3. Overstitch hem of blouse with rolled seam. Make 6 stitches with elastic thread at 1.5 cm from hem; place elastic thread from the wrong side. Distance between stitches is 1.5 cm.
4. Serge lower edge of sleeve and upper edge of blouse, turn inside onto wrong side at 4 cm. Put 2 stitches with elastic thread at 2 and 3.5 cm from the fold.

TECHNICAL DRAWING:

