

Sewing Pattern — Tunic 4265

Recommendations on fabric: natural or mixed fabric, chiffon

You will also need: fabric for decoration, elastic yarn.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowances: hem and top edge of the inset -2 cm, all other edges -1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

- 1. Front part 1 folded detail
- 2. Back part 1 folded detail
- 3. Sleeve 2 details
- 4. Front part inset 1 detail

Fabric for decoration:

- 1. Front part placket 1 detail
- 2. Back part placket 1 detail
- 3. Sleeve placket 2 details

INSTRUCTIONS:

- 1. Sew darts on front part. Press depths downwards.
- 2. Sew shoulder and side edges. Serge and press seam allowances towards back part.
- 3. Serge top edge of the inset, turn onto wrong side and topstitch. Put it right side upwards onto wrong side of the neckline and stitch. Seams will be on right side! Sew shoulder seams of plackets. Press seam allowances to back part. Overstitch the neckline with the placket. (placket connecting seams will be between front part and the placket). Turn plackets onto right side, slashing on rounded parts. Turn outer edge of plackets inside onto wrong side and topstitch.



- 4. Sew edge of sleeve. Serge and press seam allowance to back part. Sew placket of sleeve into ring, press seam allowance apart. Put placket onto the sleeve from the wrong side and stitch. Turn the placket onto right side. Turn upper seam allowance of the placket inside and topstitch. Sew the sleeve into armhole, easing in on rounded part.
- 5. Serge hem of the tunic, turn the edge inside and topstitch. Put stitches with elastic yarn.

TECHNICAL DRAWING:

