

Sewing Pattern — Blouse 5903

Recommendations on fabric: silk fabrics suitable for dresses

You will also need: elastic yarn

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: along the edge of sleeve and hem of the garment – 1.5 cm, all other edges - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Front part – 1 folded detail
2. Back part – 1 folded detail
3. Collar – 1 folded detail

INSTRUCTIONS:

1. Sew shoulder and side edges of the blouse. Serge seams and press them towards back part.
2. Sew collar into ring. Fold it in half lengthwise wrong sides together. Put parallel stitches along the collar with elastic yarn. (Elastic yarn should go on inner side of the collar). Stitch loosely at 0.5 cm off the edge and gather ruffles. Sew collar into the neckline.
3. Serge hem of sleeve, turn the edge inside and press. Put parallel stitches with elastic yarn on the sleeve edge.
4. Serge hem of the blouse, turn the edge inside and topstitch. Put the stitches with elastic yarn along the lower edge of the blouse.

TECHNICAL DRAWING:

