

## Sewing Pattern — Sarouel/Harem Pants 5902

Recommendations on fabric: natural or mixed medium to high stretch-knit fabric

You will also need: elastic thread

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams – 0,7 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

### **Advice:**

Knit fabric pieces are sewn together with special elastic or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

### Fabric:

1. Pant leg – cut 2 on fold
2. Waistband – cut 1
3. Cuff – cut 2

### **INSTRUCTIONS:**

1. Sew side and center seams of pant leg. Serge and press seams toward back. Make a gathering stitch on lower edge of pant leg and gather.
2. Fold cuffs in half, right sides together, and sew into ring. Turn cuffs right side out, fold in half lengthwise, wrong sides together, and press. Sew cuffs to lower edge. Adjust gathers to fit the length of the cuffs.
3. Mark fold line on right side of waistband. Fold belt right sides together and sew into ring. Turn right side out and press. Sew along marked line with elastic thread in the bobbin. Fold waistband along fold-line and sew to pants, slightly stretching upper edge of pants. From the fold-line of the waistband, sew rows of stitching 1.5 cm from each other using elastic thread in the bobbin.

### **TECHNICAL DRAWING:**

