

Sewing Pattern — Sari 5896

Recommendations on fabric: natural or mixed, medium to high stretch-knit fabric

You will also need: long edges of straps – 1 cm; all other edges - 1.5 cm

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all edges - 1 cm, hem of the garment – 1.5 cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric:

1. Sari – cut 1 on fold
2. Strap – cut 2

INSTRUCTIONS:

1. Fold the strap along the center, right sides together, and sew along the long side. Turn onto right side, straighten and press.
2. Sew straps to right side of the sari according to markers. Serge the sari along the contour. Turn seam allowances onto wrong side, press, and topstitch.

TECHNICAL DRAWING:

