

Sewing Pattern — Blouse 5895

Recommendations on fabric: silk

You will also need: elastic yarn, one-color companion fabric for decoration

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seam allowances - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Back part – 1 detail
2. Front part – 1 detail
3. Neckline piping – 2 details on fold
4. Back part hem piping – 1 detail
5. Front part hem piping – 1 detail
6. Side body piping – 2 details

INSTRUCTIONS:

1. Sew shoulder seams of back part and of front part, press seam onto back part and serge.
2. Sew center front edges of neckline piping, press seam allowances apart. Fold details of the piping right sides together and overstitch along inner edge. Slash seam allowances, turn onto right side and press.
3. Stitch piping to blouse neckline, slashing in corner and on folds. Press seam allowances and serge.
4. Sew corners of side body piping, hem of front part and hem of back part. Turn corners out and press. Fold piping in half lengthwise and press. Stitch piping to the blouse. Serge seam allowances and press them onto the blouse.
5. Sew side seams from hem piping connection line up to marker of the armhole, putting the stitch into piping connecting seam.
6. Stitch according to markers with elastic yarn.

TECHNICAL DRAWING:

