

## Sewing Pattern — Sarafan 5894

Recommendations on fabric: natural or mixed silk

You will also need: blind zipper, bias tape

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: top edge of back part – 2 cm, back part and front part armhole edges and top edge of front part – 0 cm, lower edge of the garment - 2 cm, all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Front part yoke – 1 detail
2. Front part belt – 1 detail
3. Lower front part – 1 folded detail
4. Back part yoke – 1 detail
5. Back part belt – 1 detail
6. Lower back part – 1 detail

### **INSTRUCTIONS:**

1. Sew darts on front part yoke. Press darts towards center of front part. Stitch front part belt to the yoke. Press the seam to the belt and serge.
2. Make counter pleat on lower front part and fix it on top edge. Stitch lower part of front part to the belt. Press the seam upwards and serge.
3. Stitch belt of back part to top part. Press the seam to the belt and serge. Sew darts on lower back part. Press darts towards center of back part. Make counter pleat according to the marking and fix it on top edge. Stitch lower back part to the belt. Press the seam upwards and serge.

4. Overstitch front part neckline and back part armhole with bias tape.
5. Press top edge of back part first at 0.7 cm, and then again at 1.3 cm and topstitch. Overstitch front part's right armhole with bias tape, make a strap, run the strap through the upper edge of back part, pipe left armhole of front part. Adjust the length of the strap when trying the garment on.
6. Serge edges of left side seam. Sew left side seam , leaving a slit for zipper at the waist level. Press the seam apart. Sew in the zipper.
7. Sew right side edge. Serge and press the seam to back part.
8. Turn lower edge of the garment twice inside at 1 cm and topstitch.

**TECHNICAL DRAWING:**

