

Sewing Pattern — Dress 5887

Recommendations on fabric: natural or mixed fabrics suitable for dresses

You will also need: invisible zipper, lining.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all edges - 1 cm, hem of the garment – 1.5 cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back - cut 1
2. Front – cut 1
3. Bow collar - cut 1

Lining:

1. Back- cut 1
2. Front part –cut 1

INSTRUCTIONS:

1. Press collar in half lengthwise, right sides together, and sew ties and section between notches (above the shoulder). Turn right side out, press.
2. Serge left side edges separately. Sew left side seam from the zipper notch downwards, press seam allowances apart, including opening for zipper. Sew in zipper. Sew right side seam, serge and press seam toward back.
3. Sew details of lining the same way as main fabric details. Pin lining to main garment, right sides together, and sew edges of the armholes, clip into curves. Turn dress right side out, press, topstitch at 0.1 cm from the edge.
4. Baste lining neck edge to garment neck edge. Make a gathering stitch along top edge of front and gather fullness.
5. Sew outer collar to upper edges of back and of front, press seam allowance of inner collar inside, and topstitch into outer collar connecting seam. Topstitch at 0.1 cm from the ties' edges at the same time.
6. Serge lower edge of dress and lining (separately), press onto wrong side and topstitch.

TECHNICAL DRAWING:

