

Sewing Pattern — Skirt 5871

Recommendations on fabric: natural or mixed fabrics (jeans fabric).

You will also need: fusing; lining; 1 zipper of 10 cm long; 2 zippers of 12 cm long; 3 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 details
2. Back part yoke – 2 details
3. Front part – 2 details
4. Pocket – 2 details
5. Back placket – 1 detail
6. Front placket – 1 detail
7. Belt – 1 detail
8. Fly catch - 1 detail
9. Belt loop - 1 detail

Lining:

1. Pocket – 2 details

Fusing: fly catch, belt.

INSTRUCTIONS:

1. Apply fusing to fly catch, belt, one-piece allowance for closure on front part.
2. Fold belt loop in half lengthwise right sides together, level edges and overstitch on long side. Turn out, straighten the seam, placing it in the center of wrong side part, and press. Put double decorative stitch at 0.1 cm and 0.7 cm on long sides. Cut belt loop detail according to the size.
3. Mark zipper location on the pocket. Apply fused bias tape to this location. Specify zipper location and cut the opening. Make cross slashes at 1-1, 5 cm off the ends. Turn seam allowances through the given slit onto wrong side, straighten edges. Put zipper under the edge so that zipper blade can be seen. Stitch the zipper.
4. Overstitch the patch pocket with lining, leaving top and side edges free. Topstitch seam allowance of pocket opening with double stitch by 0.1 and 0.7 cm off the edge.
5. Mark pocket location on front part and topstitch vertical and lower sides of pocket by 0.1 and 0.7 cm off the outer edge of pocket, leaving pocket opening free.
6. Sew darts on back part, press depths towards center and topstitch at 0.1 cm off the seam. Stitch yoke to back placket of the skirt. Press seam allowances onto yoke and put double decorative stitch by 0.1 cm and 0.7 cm off the seam. Sew center edge back part, press seam onto left side and topstitch by 0.1 and 0.7 cm off the seam.
7. Cut off one-piece allowance for closure on left front part, leaving 2 cm. Serge center edges of front plackets. Sew center edge of front part from zipper marker downwards, slash seam allowance near marker. Press seam allowances onto right side, serge and put double decorative stitch by 0.1 cm and 0.7 cm off the seam.
8. Press one-piece closure allowance on right part onto wrong side along front part center line, on left part — at 1 cm off the edge. Serge open edges of fly catch and press it along in the center wrong sides together. Stitch zipper under closure allowance edge from left side into the edge, locating zipper blade close to the fold and underlaying fly catch with the fold towards center, so that serged edge closes zipper tape. Pin the slit, aligning front part center lines. Stitch free tape of zipper to the facing of right side of the closure without catching front part fabric. Stitch the fly-piece, turning the fly catch apart. Finish the stitch, leaving 2 – 2.5 cm to center seam. Then turn fly catch onto previous place and continue the stitch up to the seam.
9. Sew side seams of the skirt up to marker slit. Slash seam allowance, press top part onto back part, press apart at slit level, and serge. Topstitch seam allowance with double stitch at 0.1 cm and 0.7 cm off the connecting seam, topstitch slit seam allowances at 0.1 cm off the fold.
10. Fold back placket in half lengthwise right sides together and overstitch short sides. Start and finish the stitch exactly near marked line of placket connection. Turn onto right side, press. Stitch outer side of the placket to back panel, turn seam allowance of inner placket inside and topstitch with double stitch at 0.1 cm and 0.7 cm off the seam.
11. Fold front placket in half lengthwise right sides together and overstitch figured sides up to marker. Turn onto right side, press, make a buttonhole. Stitch outer side of the placket to front panel, turn seam allowance of inner placket inside and topstitch with double stitch at 0.1 cm and 0.7 cm off the seam. Sew the button on back placket according to the buttonhole.
12. Fold detail of the belt in half lengthwise right sides together and overstitch short sides, turn onto right side, press. Stitch outer part of the belt to top edge, turn seam allowance of inner part inside and topstitch into connecting seam. Make buttonhole, sew the button.
13. Topstitch belt loops on belt according to the drawing, looking to the marker on top edges of back part and front part yokes.

TECHNICAL DRAWING:

