

Sewing Pattern — Dress 5863

Recommendations on fabric: velvet/velure.

You will also need: lining; blind zipper; two hooks with eyelets

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: along hem — 2 cm; all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Velvet/velure:

1. Back part – 2 details
2. Front part – 1 detail
3. Strap – 2 details

Lining:

1. Strap – 2 details

When cutting please pay attention to the nap direction. It should be directed upwards, exactly on all details. To avoid nap deformation, press seam allowance on a piece of the same velvet/velure or on thick loop towel from the wrong sides

INSTRUCTIONS:

1. Sew waist and bust darts on details of back part and of front part. Press depths of waist darts towards center of detail, depths of bust darts – upwards.
2. Serge center edge of back part. Sew in zipper from top edge up to the notch. Turn lower part of zipper and sew center edge of back part from the notch downwards. Press seam allowances apart.
3. Sew side seams, press seam onto back part and serge.
4. Overstitch main fabric straps with lining along three sides, leaving lower edge open and inserting hooks and eyelets. Slash seam allowances on rounded parts, cut a bit in corners. Turn the strap onto right side.

5. Serge seam allowance of front/back parts' armholes, press onto wrong side and topstitch.
6. Serge seam allowance of front part top edge, press onto wrong side and topstitch, underlaying the straps.
7. Serge seam allowance of lower edge, press it onto wrong side and topstitch.

TECHNICAL DRAWING:

