

Sewing Pattern — Blouson 5857

Recommendations on fabric: guipure, silk

You will also need: fusing; 2 buttons.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: hem 2 cm, all other seams 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Guipure:

1. Back part – 2 details
2. Front part – 1 detail
3. Sleeve – 2 details

Silk:

1. Facing of back part – 4 details
2. Facing of front part – 2 details
3. Big bow – 2 details
4. Small bow – 2 details
5. Strap – 1 detail
6. Pocket – 2 details
7. Cuff – 2 details

Fusing:

1. Facing of back part – 2 details
2. Facing of front part – 1 detail
3. Big bow – 2 details
4. Small bow – 2 details
5. Strap – 1 detail
6. Cuff – 2 details

INSTRUCTIONS:

1. Apply fusing to details .

2. Fold details of bows right sides together and overstitch along the perimeter, leaving a slit to turn the bow out in the center of top or lower edge (that wouldn't be seen under the strap). Slash seam allowances in corners, turn the bow onto right side, press, sew the slit.
3. Sew longitudinal edges of the strap, press seam allowances apart, placing the seam in the center of details. Topstitch upper edge of the strap onto outer facing of front part, turn the strap downwards, tack lower edge of the strap to lower edge of outer facing.
4. Apply fusing to top seam allowance of the pocket. Serge side and lower sides. Press top seam allowance of pocket onto wrong side at 1 cm, turn onto right side along fold line and overstitch corners. Turn seam allowance onto wrong side, press, also pressing side and lower seam allowances. Put decorative stitch along the fold. Topstitch pockets onto front part according to markers.
5. Stitch the front part facing to front part, catching the strap, slash seam allowances, press onto the facing.
6. Serge center edge of back part. Sew center edge from the notch downwards. Press apart the seam, pressing the slit at the same time.
7. Stitch back part facings to back part, slash seam allowances, press onto the facing.
8. Sew side and shoulder edges, press seam onto back part and serge.
9. Sew together inner facings of back part and of front part, press seam allowances apart. Fold the facing with the garment right sides together and overstitch neckline edge and seam allowance of the closure. Slash seam allowances on rounded parts, slash in corners away, turn the facing out, press. Turn lower seam allowance of inner facing inside and topstitch into outer facing connecting seam.
10. Make pleats on sleeve details (inner edges of pleats are turned from the center). Sew, press and serge edges of sleeves. Fold cuffs in half lengthwise wrong sides together and press. Unfold the cuffs and sew into ring. Press apart the seam. Fold the cuffs along fold line and stitch outer side to lower edge of sleeve. Press seam allowance onto the cuff. Turn unsewn edge of inner cuff inside and topstitch into outer cuff connecting seam.
11. Sew sleeve into the armhole. Press and serge seam allowances.
12. Press hem of the garment onto wrong side at 1 cm, then again at 1 cm and topstitch.
13. Serge buttonholes on back part facing and sew buttons. Insert bows into the strap, fasten them with several stitches.

TECHNICAL DRAWING:

