

Sewing Pattern — Dress 5829

Recommendations on fabric: natural or mixed well draping fabric suitable for dresses / thin knit fabric.

You will also need: bride or elastic yarn

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Main fabric:

1. Dress – 1 folded detail
2. Facing - 1 detail

INSTRUCTIONS:

1. Serge edges of the armhole, lower edge of the dress and side and lower edges of the facing.
2. Fold the facing with the dress right sides together and overstretch upper edge. Slash seam allowances.
3. Press seam allowance of the armhole and side edge of the facing onto wrong side and topstitch at 0.5 - 0.7 cm off the edge. Press seam allowance of lower edge onto wrong side and topstitch at 0.5 - 0.7 cm off the edge.
4. Cut a piece of elastic at 2 – 3 cm shorter than the edge of the armhole, insert it into given self-belt and fasten.
5. Turn the facing onto wrong side and topstitch onto the dress along lower edge.
6. Sew center edge of back part. Press and serge seam allowances.
7. Cut a bow of 13 cm wide and around 2 m long. Fold detail in half lengthwise right sides together and overstretch along long and one short sides. Turn the bow right side out, turn inside seam allowances of unsewn section and put decorative stitch by 0.1 cm off the edge. Advice: seam allowance of the armhole can be topstitched with elastic yarn. Bride is not needed in this case.



TECHNICAL DRAWING:

