

## Sewing Pattern — Blouse 5827

Recommendations on fabric: natural or mixed well draping fabric.

You will also need: fusing, 8 buttons.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: hem of the garment – 1.5 cm; outer edges of flounces on front part and on sleeve – 0 cm; all other seams – 1cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Back part - 2 details
2. Front part - 2 details
3. Placket – 2 details
4. Flounce of sleeve – 2 details
5. Flounce of front part – 2 details
7. Collar – 2 details
8. Stand-up part of collar – 2 details

Fusing:

1. Collar – 1 detail
2. Stand-up part of collar – 1 detail
3. Placket – 2 details

### **INSTRUCTIONS:**

1. Apply fusing to plackets, upper collar and outer stand-up part of collar.
2. Fold upper collar with lower one right sides together. Overstitch ends and fall edge of collar. Cut the seams. Turn the collar out, straighten and press. Put details of stand-up part of collar right sides touching, insert ready collar between them, level notches and sew, oversteaching ends of stand-up part at the same time. Start and finish the stitch exactly near marked line of stand-up collar connecting seam. Turn ready collar out and press.

3. Sew waist, bust and shoulder darts on details of back part and of front part. Press depths towards center of corresponding details. Cut off the depth of bust dart to 1 cm and serge.
4. Sew center edge of back part. Press seam allowances to the left and serge.
5. Serge outer edges of flounces on front part and sleeves with thin rolled seam.
6. Fold plackets with front part right side to wrong side and overstretch the edge of front band. Turn plackets onto right side, serge out and press. Turn unsewn edge of the placket inside, lay a slightly gathered flounce under it and topstitch onto front part. Fix flounce to front part along neckline and shoulder edge.
7. Sew shoulder seams, press seam allowances to back part and serge.
8. Sew upper stand-up part of collar with the collar into the neckline, turn inside open edge of lower stand-up part of collar and topstitch into stand-up part of collar connecting seam.
9. Sew flounces into the armholes. Press seam allowances onto armhole, serge and topstitch at 0.1 cm off the seam.
10. Sew side seams, press seam allowances onto back part and serge.
11. Serge hem of the garment, press onto wrong side and topstitch.
12. Serge buttonholes on right front part, sew buttons on left front part.

**TECHNICAL DRAWING:**

