

Sewing Pattern — Dress 5824

Recommendations on fabric: jeans fabric / denim

You will also need: fusing, zipper

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm, along the edge of the garment - 4 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central upper part of the front – 2 details
2. Side upper part of the front – 2 details
3. Central lower part of the front – 2 details
4. Side lower part of the front – 2 details
5. Central upper part of the back – 2 details
6. Central lower part of the back – 2 details
7. Side upper part of the back – 2 details
8. Side lower part of the back – 2 details
9. Inset of front part – 2 details
10. Inset of back part – 2 details
11. Upper collar – 1 detail
12. Lower collar – 1 detail
13. Buttonstand – 2 details
14. Sleeve – 2 details
15. Cuff – 2 details
16. Pocket flap – 4 details
17. Pocket facing – 4 details

Lining:

1. Lower lining of pocket – 2 details
2. Top lining of pocket - 2 details

Fusing: buttonstand, back neckline facing, upper collar

INSTRUCTIONS:

1. Apply fusing to buttonstand, back neckline facing, upper collar.
2. Fold upper collar with lower one and overstitch on ends and outer edge, starting and finishing the stitch exactly near marked line of collar connecting seam. Slash away seam allowances in corners, turn collar right side out. Straighten seams and press collar.
3. Stitch side upper part of the back to central upper part of the back. Press seam onto central part and serge. Put decorative stitches at 0.1 and 0.5 cm off the connecting seam. Stitch inset of back part to upper part, press seam onto inset and serge. Stitch side lower part of the back to central lower part of the back. Press seam onto central part and serge. Put decorative stitches at 0.1 and 0.5 cm off the connecting seam. Stitch lower part of the back to the inset, press seam onto inset and serge.
4. Fold facing of pocket in half lengthwise wrong sides together and press. Mark additional line on pocket facing parallel to the facing fold to connect it. Mark additional line on the flap to connect it parallel to top edge of the flap, measuring flap width on the whole length. Mark additional lines parallel to pocket opening to connect the flap and facings of pocket. Stitch lining of pocket to the flap. Stitch facings to the front. Finish the stitches near parallel lines of pocket marking. Check you stitched facings correctly on the wrong side (stitches should be parallel). Cut the pocket opening. Make cross slits at 1-1,5 cm off the end of pocket. Turn facings wrong side out through the given slit; straighten edges, adjust ends of the facings so that pressed folds of the facings come line-on-line to each other. Fix ends of pocket on the wrong side with double back stitch on corners basing. Stitch lining of pocket to the flap. Insert the flap into pocket and stitch to top facing of pocket. Stitch lower lining of pocket into lower facing connecting seam; cut and sew lining of pocket. Serge lining of pocket.
5. Sew center edge of the back. Press seam onto left side and serge. Put decorative stitches on the back at 0.1 and 0.5 cm off the connecting seam.
6. Stitch side upper part of the front to central upper part of the front. Press seam onto central part and serge. Put decorative stitches at 0.1 and 0.5 cm off the connecting seam. Stitch inset of front part to upper part, press seam onto inset and serge. Stitch side lower part of the front to central lower part of the front. Press seam onto central part and serge. Put decorative stitches on the front at 0.1 and 0.5 cm off the connecting seam. Stitch lower part of the front to inset, press seam onto inset and serge.
7. Sew shoulder and side edges of the dress. Press seam allowances towards back part and serge. Put decorative stitches on insets at 0.1 and 0.5 cm off the connecting seam.
8. Fold fronts right sides touching and level edges, measuring the length of buttonstands. Stitch zipper to buttonstand edge. Turn inside edges of buttonstand on zipper section and press. Put buttonstand onto right side of the front right side downwards, pin together and overstitch along buttonstand. Overstitch from side of the front upwards up to collar connecting marker. Stitch lower edges of buttonstands to the front exactly along marked line of hem turnout. Cut seam allowances of lower corners of buttonstand. Slash seam allowances in corners. Бопра turn front bands right side out, straighten seams.
9. Sew, press apart and serge shoulder edges of back part and buttonstand neckline facing. Serge open edge. Sew lower collar into the neckline of the dress, and top collar into edge of back part and buttonstand neckline facing. Slash corner on the front and on buttonstand. Press apart allowances of connecting seams of collars and fix close to seams. Put decorative stitches at 0.1 and 0.5 cm along buttonstand edge, lapel and collar.
10. Sew, serge and press sleeve seam. Stitch loosely on rounded part of sleeve. Make a gathering exactly from notch up to notch. Sew sleeve into armhole. Serge edge of the armhole. Stitch loosely along hem of sleeve. Gather hem of sleeve according to the length of cuff. Serge long edge of cuff.

Sew cuff into ring. Stitch it to hem of sleeve, press seam onto cuff. Turn free edge of cuff inside the sleeve. Put decorative stitches on cuff at 0.1 and 0.5 cm off the connecting seam.

11. Serge lower edge of the dress, press onto wrong side and topstitch with two parallel decorative stitches.

12. Serge long edges of belt loops. Turn inside seam allowances and topstitch with two parallel stitches. Topstitch belt loops onto the dress, turning seam allowance inside with small zig-zag stitch. Topstitch belt loop onto inset with cross stitch, distributing the slack evenly.

13. Cut 2 belts of 6 cm wide, and as long as the waist plus 20 cm. Press in half lengthwise, turning seam allowances inside. Put decorative stitches at 0.1 cm off the belt edges. Put the clasp on the belt. Run the belt through belt loops.

