

Sewing Pattern — Dress 4254

Recommendations on fabric: fabrics suitable for dresses

You will also need: blind zipper, fusing, 2 hooks with eyelets

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm; hem of the dress – 2.0 cm, along the vent – 6 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central back part - 2 details
2. Side back part - 2 details
3. Upper side part of the front – 2 details
4. Lower side part of the front – 2 details
5. Central front part - 1 detail
6. Collar – 1 detail
7. Off-set welt – 2 details
8. Sleeve - 2 details
9. Lining of sleeve - 2 details
10. Lining of pocket - 2 details
11. Strap - 1 detail
12. Bow - 1 detail

Fusing:

1. Off-set welt — 2 details

INSTRUCTIONS:

1. Apply fusing to off-set welts.
2. Sew princess seams on back part, press seam allowances to center seam and serge.
3. Cut off 5 cm on left part of the back along vertical edge of the vent. Apply fusing to wrong side of the vent on both details of the back. Mark center seam line (vent fold line) on the right side. Press left part along vent fold line, on right part press only seam allowance of right side of the vent (6 cm)

onto wrong side. Align details along center seam and fix along top edge of the vent. Serge center edge of the back separately on each detail. Serge seam allowances of the vent. Sew center edge of the back from closure marker up to vent corner. Slash corner of vent seam allowance on right part. Press allowances of center seam apart, press vent seam allowances and fix them along right side with machine stitch. Sew in zipper.

4. Press off-set welt in half lengthwise wrong sides together. Fold lining of pocket with lower part of the front right sides together, insert off-set welt between them and sew. Turn lining onto wrong side, straighten off-set welt, press. Put lower part of the front onto upper part and sew lower edge of lining of the pocket, serge. Fix lining of pocket to side and princess seams.

5. Sew princess edges of the front, press seam allowances towards center and serge.

6. Sew side and shoulder edges, press seam onto back part and serge.

7. Fold strap in half lengthwise right sides together and overstitch long side. Turn onto right side, press, placing seam in the center of detail.

8. Overstitch ends of collar, inserting hooks and eyelets, and starting and finishing the stitch exactly near collar connecting line. Slash seam allowances in corners. Turn collar onto right side, straighten, press. Sew outer side of collar into the neckline, inserting lower side of the strap between details, turn inner side inside and topstitch into connecting seam. Envelope collar with the strap, fasten on wrong side. Fold ends of collar in half lengthwise and sew ends of collar to connecting seam.

9. Make pleats on the sleeve according to markers. Fold sleeve with lining right sides together and overstitch lower edge. Unfold sleeve and sew edge of sleeve and edge of lining with one seam. Press apart the seam. Turn lining onto wrong side, fix along rounded part. Sew sleeve into armhole, leveling notches and easing in on rounded part. Press seam allowances and serge.

10. Serge seam allowance of the dress hem, press onto wrong side and undersew with invisible stitches. Fix seam allowance of the vent to hem turnout.

11. Fold the bow in half lengthwise right sides together and overstitch along three sides, leaving a slit to turn out. Turn detail onto right side, sew the slit. Run the bow through the strap, fasten with several stitches.

TECHNICAL DRAWING:

