

Sewing Pattern — Lingerie 5791

Recommendations on fabric: silk or silk-like

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges. Hem – 1.5 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Back – cut 1
2. Front – cut 1
3. Back facing – cut 1
4. Front facing – cut 1

INSTRUCTIONS:

1. Mark and sew darts on front. Press the darts toward hem.
2. Sew side seams. Serge and press toward back.
3. Sew side seams of facings, press apart and serge edges. Serge lower edge of facings.
4. Cut a strips of bias tape from the main fabric, 3 cm wide and 70 cm long. Fold in half lengthwise, right sides together and sew long side 0.5 cm from the edge. Turn right

side out and straighten.

5. Pin straps to the garment and adjust according to technical drawing.

6. Pin facing and garment right sides together, and sew upper edge, inserting the straps. Clip into curves, understitch, turn facing right side out, straighten and press. Topstitch facing to garment at 0.5-0.7 cm from the edge.

7. Serge lower edge of garment, turn onto wrong side, and topstitch.

TECHNICAL DRAWING:

