

## Sewing Pattern — Lingerie 5790

Recommendations on fabric: chiffon, stretch lace

You will also need: decorative ring for strap, diameter appr. 2.5 cm, decorative elastic

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance 1 cm on all seams; upper edge of front – 2 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

#### Fabric:

1. Lower back – cut 1
2. Upper front – cut 2
3. Lower front – cut 1

#### Stretch lace:

1. Inset for back – cut 1
2. Inset for front – cut 1

### **INSTRUCTIONS:**

1. Sew lower back to inset, serge and press allowances onto inset. Serge upper edge of back inset.
2. Serge upper, side, and front edges of upper front. Press allowances of side and front edges onto wrong side and topstitch. Fold upper seam allowance onto wrong side, insert decorative ring and topstitch.
3. Make a gathering stitch along the lower edge of upper front and gather fullness. Sew upper front to front inset between notches, serge and press seam allowances downwards.
4. Sew lower front to inset, serge and press allowances onto inset.

5. Serge side edges separately. Sew side seams from top to marker. Press seams apart, pressing the slit at the same time. Topstitch the slit 0.1 cm from the edge.
6. Press seam allowance of upper edge onto wrong side, insert elastic and stitch with zigzag stitch.
7. Serge lower edge of garment, press to wrong side and topstitch.
8. Cut two straps of required length and 5 cm wide. Fold the strap in half lengthwise right sides together and sew the long side. Turn the strap right side out and press. Serge short edges. Thread one end of strap through the ring and topstitch onto strap with zigzag stitch. Adjust straps and sew to center back.

**TECHNICAL DRAWING:**

