

## Sewing Pattern — Lingerie 5788

Recommendations on fabric: elastic lace with scallops, microfibre.

You will also need: elastic band 0.5 cm wide, ready straps.

If the pattern has double contour, seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance 1 cm on all edges.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

### **CUTTING:**

Fabric:

1. Back part – 1 detail.
2. Side front part – 2 details
3. Lower front part – 1 detail

Lace:

1. Upper right front part – 1 detail
2. Upper left front part – 1 detail



Advice: use special elastic seam or zigzag seam to stitch the parts together. When overstretching, cut the seam allowances to 0.6 — 0.8 cm. The seam allowance on the edge of the garment is stitched with double seam to ensure stretchiness.

### **INSTRUCTIONS:**

1. Sew lower front part to upper front part, serge the seam allowances cutting them to 0.5 cm.
2. Sew cup off upper right front part to side front part, serge the seam allowances cutting them to 0.5 cm.
3. Sew dart on cup, at the same time sewing relieve seam, serge the seam allowances cutting the dart depth to 0.5 cm.
4. Serge lower edge of upper left front part. Put upper right front part onto upper left front part and topstitch along scallops.
5. Sew cup of upper left front part to side front part, serge the seam allowances cutting them to 0.5 cm.
6. Sew dart on cup, at the same time sewing relieve seam up to marker, serge the seam allowances cutting them to 0.5 cm.
7. Serge edges of slit with rolled seam, cutting away seam allowance.
8. Sew side seams, serge the seam allowances cutting them to 0.5 cm.

9. Serge armholes and upper edge of back part with rolled seam. To prevent the details from stretching topstitch elastic band from the wrong side with zigzag stitch stretching the band a bit. The elastic band should be 10% cm shorter than the detail. **TECHNICAL DRAWING:**

