

## Sewing Pattern — Lingerie 5787

Recommendations on fabric: natural / mixed well draping silk fabrics

You will also need: lace ribbon of 7cm wide with festoon on both sides.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams -1 cm, along the edge of stand front part – 0 cm .

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Main fabric:

1. Central back part – 1 detail
2. Side back part – 2 details
3. Side front part - 2 details
4. Central front part - 2 details
5. Sleeve - 2 details

### **INSTRUCTIONS:**

1. Put lace on front part along the marked line and topstitch its inner edge from right side with small zig-zag stitch. Cut carefully extra fabric from wrong side close to the stitch.
2. Cut bias tape of 4 cm wide and length equal to the length of back part neckline. Press bias tape in half lengthwise, wrong sides together. Fold bias tape with back part neckline seam allowance right sides together and overstitch. Turn the bias tape onto wrong side. Topstitch seam allowance onto the bias tape with a 0.1 cm wide stitch. Stitch the neckline of back part with 0.7 cm wide stitch.
3. Sew relieve seams of back part and of front part. Press seam allowances towards center and serge.
4. Sew side and shoulder edges, press seam onto back part and serge.
5. Put lace onto the sleeve along the marked line and topstitch its inner edge from right side with small zig-zag stitch. Cut carefully extra fabric from wrong side close to the stitch. Make a beautiful plait with the lace on rounded part and fasten.

6. Sew and serge edge of sleeve.
7. Sew sleeve into the armhole. Serge.
8. Serge seam allowance on hem of the garment and of sleeve, press onto wrong side and topstitch.
9. Cut two ties from main fabric, width is 3 cm and length is approximately 25 cm. Fold them in half lengthwise right sides together and overstitch on long side on 0.5 cm off the edge. Turn ties onto right side, straighten and sew to front stand.

**TECHNICAL DRAWING:**

