

Sewing Pattern — Lingerie 5786

Recommendations on fabric: silk fabric and guipure.

You will also need: elastic band 0.5 cm wide, decorative cord.

If the pattern has double contour, seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance 1 cm on all edges.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Fabric:

1. Back part – 1 detail.
2. Lower front part – 2 details

Guipiure:

1. Upper front part – 2 details

INSTRUCTIONS:

1. Mark and sew darts on upper front parts. Serge, cutting away the darts' depths.
2. Sew upper front parts together, serge and press the seam allowances.
3. Serge neckline and upper edge of upper front part, turn to the wrong side, press and topstitch. To prevent the upper front part from stretching topstitch elastic band from the wrong side along neckline and outer edge with zigzag stitch, stretching the band a little bit. The band should be 10% shorter than the detail.
4. Serge the hem, turn to the wrong side and press.
5. Sew upper front part to lower front part. Sew side seams. Press seam allowances to the back piece and serge. Serge seam allowances of the seam connecting upper and lower front parts, continue on remaining upper edge of front part and back part.
6. Turn seam allowance of upper edge to the wrong side, press and topstitch.
7. Serge hem, turn to the wrong side, press and topstitch.
8. Cut decorative cord in 4 parts, sew to the edge on front part.



TECHNICAL DRAWING:

