

Sewing Pattern — Lingerie 5783

Recommendations on fabric:

silk fabric suitable for dress, elastic guipure with scallops

You will also need: elastic inkle 0.5 cm wide, decorative braid, ready straps.

Seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges. Seam allowance on middle edge of front piece – 0 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Upper back part – 1 detail.
2. Lower back part – 1 detail.
3. Side front part – 2 details.
4. Lower front part – 2 details.

Guipure:

1. Upper front part – 2 details.

Advice: use special elastic seam or zigzag seam to stitch the parts together. When overstretching, cut the seam allowances to 0.6 — 0.8 cm. The seam allowance on the edge of the garment is stitched with double seam to ensure stretchiness.

INSTRUCTIONS:

1. Mark and sew darts on upper front part. Serge the seam, cutting the depths of darts.
2. Sew side front part to upper front part, serge the seam.
3. Cut a flounce 6 cm wide and of the length mentioned on the pattern for back part from main fabric. Cut it in two, serge the long side with rolled seam, stitch loosely along the other long side. Gather ruffles until the length equals that of the edge of lower front part, sew flounce to garment and serge the seam.
4. Sew lower front part to upper front part, serge the seam.
5. Cut a flounce 6 cm wide and of the length mentioned on the pattern for back part from main fabric. Cut it in two, serge the long side with rolled seam, stitch loosely along the other long side. Gather ruffles until the length equals that of the edge of lower back part, sew flounce to garment and serge the seam.
6. Sew and serge side seams.
7. Serge upper edge of back and front parts, press to the wrong side, put the elastic inkle under the seam allowance, stretching it slightly so that the inkle is 10% shorter than the seam. Topstitch with zigzag stitch.
8. Sew on ready straps. Sew on band.

TECHNICAL DRAWING:

