

## Sewing Pattern — Lingerie 5781

Recommendations on fabric: thin silk fabric.

You will also need: decorative trim, elastic band 0.5 cm wide.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges, seam allowance on hem – 2.4 cm. Seam allowance of upper edges of back, front part and sleeve — 3.5 cm. Sleeve hem – 3.5 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.

### **CUTTING:**

Main fabric:

1. Back part – 1 detail
2. Front part – 1 detail
3. Sleeve – 2 details

### **INSTRUCTIONS:**

1. Sew in sleeves into armholes of back part. Press seams onto sleeve and serge.
2. Sew in sleeves into armholes of front part. Press seams onto sleeve and serge.
3. Sew with one seam edges of sleeve and side edges. Press towards back part and serge.
4. Serge seam allowance of upper edge, press onto wrong side and topstitch half-belt according to markers, leaving a slit for threading in elastic band. Cut a piece of elastic band of the required length and thread into half-belt.
5. Serge seam allowance of lower edge of sleeve, press onto wrong side and topstitch half-belt according to markers, leaving a slit for threading in elastic band. Cut a piece of elastic band of the required length and thread into half-belt.
6. Press hem of garment onto wrong side, turn inside and topstitch.
7. You may make bows from decorative trim and sew onto garment as in picture.



**TECHNICAL DRAWING:**

