

Sewing Pattern — Lingerie 5774

Recommendations on fabric: chiffon, panne

You will also need: bias tape; ready straps

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm; on top edge of top front part and top back part, on armholes edges, along the edge of lower back part and lower front part - 0 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Chiffon:

1. Lower back part — 1 folded detail
2. Lower front part — 1 folded detail

Panne:

1. Upper back part – 1 folded detail
2. Upper front part - 1 detail

INSTRUCTIONS:

1. Cut a slit on top front part and pipe it with bias tape. Serge upper edge of top front part with dense rolled stitch. Make plaits according to markers, lay bias tape on front part by 2 cm off top edge and topstitch it, fixing plaits by that. Shape a bow from bias tape and fix edge of slit with it.
2. Stitch lower front part to top part. Press seam allowances upwards and serge.
3. Stitch lower back part to top part, press seam upwards and serge.
4. Sew side seams. Press seam allowances towards back part and serge.
5. Press bias tape longwise in the middle and pipe edges of the front part armhole and upper edge of back part.
6. Overstitch lower edge with thin rolled seam.
7. Sew straps.

TECHNICAL DRAWING:

