

Sewing Pattern — Lingerie 5773

Recommendations on fabric: silk, light-weight, transparent fabric of natural or mixed fiber.

You will also need: ready straps, ribbon 1.5 cm wide, decorative elastic braid

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: on the bottom edge of the front and back and the upper part of the inset on the front - 0 cm. Stay stitch 1 cm on all edges.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Fabric:

1. Back - cut 1 (symmetrical)
2. Front — cut 1 (symmetrical)
3. Front inset - cut 1

Advice: you can cut the inset from a fabric with lace edge, otherwise the upper edge should be serged, then folded, and topstitched



INSTRUCTIONS:

1. Make a gathering stitch along the armhole edges of the front inset —0.8 cm from the edge. Gather fullness to the mentioned length.
2. Repeat for the upper edge of the front. Sew the inset to the front, serge and press seam allowances upwards.
3. Sew the side seams. Serge and press seam toward back
4. Serge the upper edge of the back and front. Press the seam allowance to the wrong side, place the elastic between the seam allowance and the main part (the length of the elastic is mentioned on the back piece) and stitch with a zigzag seam, stretching the elastic to the length of the upper edge.
5. Cut a casing from main fabric — the width is 4 cm, the length is mentioned on the back piece. Press the edges under, pin it onto the front side of the garment following the markers and stitch close to folded edges, leaving the short sides unsewn. Thread the ribbon through it.
6. Serge the lower edge of garment with a rolled seam.
7. Sew the straps to the garment, using the technical drawing as a guide.

TECHNICAL DRAWING: