

Sewing Pattern — Blouse 5768

Recommendations on fabric: natural/mixed fabric (cotton, viscose, polyether)

You will also need: trimming; 3 hooks and 3 loops

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Upper back part – 2 pieces
2. Lower back part – 1 piece
3. Upper front part – 2 pieces
4. Lower front part – 2 pieces

Trimming:

1. Back yoke – 1 piece
2. Front yoke – 2 pieces

INSTRUCTIONS:

1. Cut a fabric piping of 4 cm width for flounces. See piping length on patterns. Stitch around one edge. Make a seam with loose stitches along another edge and gather fabric a little.
2. Stitch upper back darts. Press darts toward back center. Stitch back middle seam. Neaten and press it.
3. Make a seam with loose stitches along upper part's lower edge between notches. Gather the fabric.
4. Stitch yokes along side seams. Neaten the seam and press it backward. Stitch a flounce to yoke's lower edge.

5. Stitch shoulder edges of front/back parts. Neaten seams and press them backward. Stitch flounces to armholes. Stitch side seam of upper front/back parts. Neaten the seam and press it backward.
6. Stitch side seams of lower back/front parts excluding a segment in left side seam between the hem and 5 cm mark. Neaten right seam and press it backward, neaten left side seam and press it apart.
7. Stitch upper/lower parts to the yoke. Neaten seams and press them toward the yoke.
8. Sew loops to left front edging. Stitch the flounce along the contour. Begin and finish stitching at side slit. Stitch side seam to the hem. Sew hooks on right front edging above the flounce.

TECHNICAL DRAWING:

