

Sewing Pattern — Blouse 5764

Recommendations on fabric: lace, lightweight, sheer.

You will also need: 2 lace trims: 2 cm wide and 4-5 cm wide

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm on all edges

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Back – cut 1
2. Front – cut 1 on fold
3. Sleeve – cut 2
4. Flounce – cut 2

INSTRUCTIONS:

1. Make the first pleat on the front with its wrong side inside and its folding out. Stitch the pleat on right side between the neckline and crosswise mark. Do the same for other pleats. Press pleats toward front center as shown in the picture. Baste to neck edge.
2. Sew back darts. Press darts toward back center.

3. Sew right shoulder seam. Finish or serge seam and press toward back. Finish or serge seam allowance along the neckline. Sew 2 cm wide trim on neckline edge. Sew left shoulder seam. Finish or serge the seam and press it toward back. Sew side seams. Finish or serge seam and press toward back.
4. Sew flounces to sleeves. Finish or serge seams and press them upward. Stitch 4-5 cm wide trim on the seam. Topstitch 2 cm wide trim along flounce hem. Sew sleeve edges, finish or serge seam and press open. Sew a gathering stitch along cap of sleeve to adjust ease. Sew sleeves into armholes, matching marks and easing along sleeve caps.
5. Finish or serge hem. Topstitch 4-5 cm wide trim along blouse hem.

TECHNICAL DRAWING:

