

## Sewing Pattern — Blouse 5758

Recommendations on fabric: soft silk/viscose

You will also need: fusible interfacing

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 1.5 cm for garment/sleeve hems

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

### **Fabric:**

1. Front – cut 2
2. Back – cut 2
3. Stand-up collar – cut 2
4. Belt – cut 2
5. Sleeve – cut 2

### **Interfacing:**

1. Stand-up collar – cut 1

## **INSTRUCTIONS:**

1. Apply the interfacing to outer collar.
2. Sew upper front darts. Press darts toward hem. Sew wrap darts as marked, press downward.
3. Sew back darts. Press darts toward center. Sew center back seam. Serge and press toward left.
4. Serge side edges separately. Sew side seams, leaving an opening in the right seam for belt. Press seam apart. Topstitch stitch at 0.1 cm along the opening in the right seam. Sew shoulder seams, serge and press toward back.
5. Pin stand-up collar, right sides together, and sew, stopping at connecting seam. Trim corners and turn the collar right side out and press.
6. Clip front between shoulder seam and the mark. Serge diagonal edge of self-facing on front. Sew outer collar to back neckline, right sides together, between marks. Turn self-facing, right sides together, over front and collar inner/outer front edges and sew. Trim seam allowance at corner. Turn the self-facing of front under, and tack it to the collar/shoulder seam. Turn under the remaining inner collar seam allowance and topstitch along the seam joining the outer collar. Press.
7. Fold the belt along the center, right sides together, and sew long edge and one short edge. Turn right side out, and press.
8. Insert belts between the front self-facing and front. Sew all with one seam. Serge seam, turn the front self-facing under. Serge edge on the segment between the waistband and the hem, turn under and topstitch.
9. Sew sleeve seams, serge and press. Make a gathering stitch between notches, gather fullness slightly. Sew sleeves into armholes, matching notches and adjusting gathers. Serge seam and press toward garment.
10. Serge bottom edge of garment, press under, and topstitch.

## **TECHNICAL DRAWING:**

