

Sewing Pattern — Jacket 5745

Recommendations on fabric: natural or mixed suiting fabric

You will also need: fusible interfacing; lining; raglan shoulder pads; 2 buttons.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 3.5 for hems

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Back – cut 2
2. Front – cut 2
3. Collar – cut 2
4. Collarstand – cut 2
5. Lapel – cut 4
6. Back neck facing – cut 1
7. Front band/facing – cut 2
8. Front sleeve – cut 2
9. Back sleeve – cut 2
10. Belt - Cut 1

Lining:

1. Back –cut 2
2. Front – cut 2
3. Front sleeve – cut 2
4. Back sleeve – cut 2

Interfacing:

1. Front band/facing - cut 2
2. Back neck facing - cut 1
4. Collar – cut 1
5. Collarstand – cut 1
6. Lapel – cut 2

* lining pieces are cut using main pattern pieces excluding the width of back neck facing and front band/facing.

INSTRUCTIONS:

1. Apply the interfacing to back neck facing, front band/facing, front, outer collar, outer collarstand and outer lapel.
2. Sew darts on back and press toward center. Sew darts on front and press toward center.
3. Sew back center seam, press seam open. Sew back sleeves to back. Sew front sleeves to front parts. Press seams open.
4. Stitch sleeve upper edges. Press seams open. Sew side seam and sleeve seam together as one. Press seams open.
5. Sew collars right sides together. Trim the corners. Turn the collar right side out and press. Place collarstands, right sides together, insert ready collar, match notches and sew together including collarstand ends. Turn the collarstand right side out and press it.
6. Sew lapels right sides together, leaving neckline joining edge. Trim the seam. Turn the lapel right side out and press it.
7. Sew the collar and the lapels to the jacket. Press seams apart.
8. Sew shoulder edges of back neck facing/front band/facing. Press seams apart.
9. Pin the front band/facing on the front, right sides together, and sew to front and neckline. Understitch on the front band, at 0.2 cm from the seam. Turn facing to wrong side, press.
10. Stitch lining pieces, leaving an opening in right seam of sleeve for turning.
11. Press garment/sleeve hems under. Sew shoulder pads. Sew the lining to inner edges of front band/facing and back neckline facing. Sew front edging's lower corner. Trim front lower corner seams. Sew the lining to jacket/sleeve hems. Turn the jacket right side out through the opening in the sleeve. Slipstitch the opening closed.
12. Make buttonholes on right front edge, sew buttons on the left one.
13. Fold the belt along the center, right sides together. Sew it along long and one short side. Turn the belt right side out, fold open short side end to inside and slipstitch closed. Topstitch at 0.1 cm along belt's outside edges. Sew the belt to left side seam.

TECHNICAL DRAWING:

