

Sewing Pattern — Coat 4248

Recommendations on fabric: gabardine

You will also need: fusible interfacing; lining; shoulder pads; 5 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams -1 cm; hem of the garment and of sleeve - 3.5 cm; along edges of pocket bags – 2 cm; along the edge of lining 2 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Back neck facing (upper back) – cut 2
2. Back – cut 1 on fold
3. Front neck facing (upper front) – cut 4
4. Front – cut 2
5. Front band facing – cut 2
6. Upper sleeve – cut 2
7. Lower sleeve – cut 2
8. Belt – cut 2
9. Upper collar – cut 1
10. Lower collar – cut 1
11. Collar placket – cut 2
12. Bow – cut 1
13. Bow knot (belt loop) – cut 1
14. Off-set welt – cut 2
15. Large pocket bag – cut 2

Lining:

1. Small pocket bag – cut 2
2. Back – cut 1 on fold
3. Front – cut 2
4. Upper sleeve – cut 2
5. Lower sleeve – cut 2

*ATTENTION: Lining is cut using main fabric patterns excluding the width of front band facing. Add a pleat on lining.

Fusible interfacing: front band facing, off-set welt, upper collar, bow, front, upper front

INSTRUCTIONS:

1. Apply interfacing to listed pieces.
2. Fold off-set welt in half lengthwise, right sides together, and sew side edges. Turn off-set welt out and press. Make a decorative stitch along the contour at 1 cm from the edge. Mark the line on off-set welt, determining the width of off-set welt when ready. Topstitch small pocket bag onto inner side of off-set welt, matching along center. Pin off-set welt onto front at marking line right sides together. Sew off-set welt. Sew large pocket bag to other pocket marking line. Cut the pocket opening in the center between marking lines, making diagonal snips to corners of pocket marking. Turn onto wrong side through pocket entrance. Straighten seam allowances and press. Sew edges of pocket bags, fixing corners of pocket. Mark a line on off-set welt at 5.5 cm from the fold. Fold off-set welt along marked line. Fasten off-set welt to front with 2-3 stitches in four corners.
3. Sew bust dart on front. Press toward hem. Make and sew a counter pleat on back according to markers. Press.
4. Sew side and shoulder seams of back and front. Press seam apart and serge.
5. Sew together, pairwise, back and front neck facings. Press seams apart. Pin right sides together and sew neckline edge. Clip into curves, turn right side out, and press.
6. Fold the bow in half lengthwise, right sides together, and sew along three sides, leaving a slit in the center of the long side for turning out. Turn right side out and press. Sew the slit closed. Make a decorative stitch along long sides at 1 cm from the edge.
7. Fold bow knot (belt-loop) in half lengthwise, right sides together, and sew long side. Turn right side out and press, placing the seam in the center. Make a decorative stitch along long sides at 1 cm from the fold.
8. Topstitch the bow onto right side of upper collar from the right side, aligning marked lines. Sew the bow knot (belt-loop) to upper collar, aligning upper and lower edges. Sew upper collar to the neckline. Clip into curves and press seam apart.
9. Pin lower collar to collar placket right sides together. Insert vertical edge of front neck facing between them, matching notches along the lower edge. Sew together. Press seam toward the placket. Fix lower collar to facing along the lower edge.
10. Sew lining the same way as main fabric pieces. Turn seam allowance of the lining hem twice inside at 1 cm and topstitch. Sew lining to front band facing. Press seam allowances onto lining and serge. Sew lower collar to lining and to front band facing. Press seam onto lining.
11. Sew and press sleeve elbow seam. Make a decorative stitch at 1 cm off the seam. Press hem of sleeve. Sew and press apart front sleeve seam. Make a gathering stitch along sleeve cap for ease. Sew sleeve into armhole, matching notches and adjusting ease. Sew in shoulder pads.
12. Serge lower edge of garment. Press hem. Pin lining to facing and lower collar, with right sides together, sew facing and upper edge of collar. Sew lower edges of front band facing to front exactly along marked line of hem turnup. Trim corners. Turn coat out onto right side, straighten and press seams. Put fixing stitch along collar and neckline connecting seam.

13. Make a decorative stitch at 1 cm from the edge of center front / collar: from hem of the garment up to top corner of collar, then along top edge of collar, stop the stitch under the bow knot (belt-loop), move the coat, and continue the stitch to hem line. Make a decorative stitch on collar along connecting seam at 1 cm from the seam. Sew the stitch in two steps: up to front neck facing connecting seam, then stop the stitch and sew through up to front stand edge.
14. Sew lining to hem of sleeves. Turn coat onto right side.
15. Sew hem with invisible stitches. Make buttonholes on right front, sew buttons on left front .
16. Fold belt, right sides together, and sew along contour, leaving a slit in the center of 10-15 cm long for turning out. Turn belt right side out, turn seam allowances of unsewn section inside and sew by hand. Make a decorative stitch at 1 cm from the edge along the perimeter of the belt. Make buttonholes on the belt, sew buttons on back. Button the belt.

TECHNICAL DRAWING:

