

Sewing Pattern — Youth-Looking Jacket 5711

Recommendations on fabric: faux sheepskin with short hair.

You will also need: leather braid (trimming), 1 button.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 0 cm for front edgings/lapel edges/garment hem /cuff lower edges/collar fall/collar corners as well as all center/side back/front lower edges and sleeve hems, 0.5 cm for collar joining seam, 1.5 cm for other seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Sheepskin:

- 1. Side upper front part 2 pieces
- 2. Side upper back part 2 pieces
- 3. Center upper back part 2 pieces
- 4. Center upper front part 2 pieces
- 5. Lower back part 1 piece
- 6. Lower front part 2 pieces
- 7. Collar 1 piece
- 8. Sleeve 2 pieces
- 9. Cuff 2 pieces

INSTRUCTIONS:

NB! Lower front/back parts, cuffs and collar right side: fur; other pieces: suede.

- 1. Stitch upper front/back relieves. Lay seam allowances apart. Topstitch a piece of leather braid above relieves (right side) catching seam allowances.
- 2. Mark decorative line on lapel's fur side: between the notch pointing collar joining end and lapel folding line. Topstitch leather braid along marked line.
- 3. Stitch middle back edges. Lay seam allowances apart.
- 4. Stitch upper side edges. Lay seam allowances apart.
- 5. Stitch lower side edges excluding 5 cm segment in left side seam. Lay seam allowances apart and



paste them.

- 6. Stitch upper/lower parts together with lapel seams. Topstitch a piece of leather braid above seams.
- 7. Stitch shoulder edges. Lay seam allowances apart.
- 8. Stitch sleeve seams. Cut seam allowances close to stitches.
- 9. Trim cuff edges with braid. Coincide cuff ends and marks, then stitch cuffs as rings. Stitch cuffs to sleeves with lap seams.
- 10. Stitch sleeves into armholes according to notches.
- 11. Trim collar's open edges.
- 12. Lay the collar on the garment suede sides together. Stitch the collar to the garment with zig zags. Do not fold the collar out and trim with leather braid: (begin at left lower side seam) left front edging, left lapel edge, collar joining edge, right lapel edge, right front edging, back hem, stop at left side seam. Stitch a segment in left side seam. Paste seam allowances.
- 13. Make a buttonhole into right front edging, sew a button on the left one.

TECHNICAL DRAWING:

