

Sewing Pattern — Skirt 5696

Recommendations on fabric: sheer natural/mixed fabric

You will also need: fusible interfacing; invisible zipper

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 2 cm for the hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Fabric:

1. Back skirt_1 - cut 1
2. Back skirt_2 - cut 1
3. Back skirt_3 - cut 1
4. Back skirt_4 - cut 1
5. Front skirt_1 - cut 1
6. Front skirt_2 - cut 1
7. Front skirt_3 - cut 1
8. Front skirt_4 - cut 1
9. Back facing - cut 1
10. Front facing - cut 1

Fusible interfacing: front/back facings

INSTRUCTIONS:

1. Apply the fusible interfacing to wrong side of facings.
2. Sew front skirt_1 to front skirt_2. Serge and press seam toward skirt_1.
3. Stitch front skirts_2 and 3 together. Serge and press seam toward skirt_2 .
4. Stitch front skirt_4 to front skirt_3. Serge and press seam toward skirt_3 .
5. Repeat steps 2-4 for back skirt.
6. Serge left side edges separately. Sew left side seam between zipper mark and the hem. Press the seam apart including zipper opening. Sew in zipper.
7. Sew skirt's right side seam. Serge and press seam toward back.
8. Sew side seams of facings, press seams apart. Serge lower edge. Pin facing to skirt upper edge, right sides together, and sew. Understitch, turn onto wrong side, and press. Tack at side seams and slipstitch to zipper tape.
9. Serge lower edge of garment, turn under, and topstitch.

TECHNICAL DRAWING:

