

## Sewing Pattern — Top 5672

Recommendations on fabric: middle/high stretchable jersey (natural or mixed)

You will also need: decorative braid (for a coulisse).

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1.5 cm for the hem/sleeve hems, 1 cm for other seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Back part – 1 piece
2. Front part – 1 piece
3. Sleeve – 2 pieces
4. Placket – 1 piece

**Our advice:** stitch jersey details with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances till 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

### **INSTRUCTIONS:**

1. Stitch the sleeve to front part. Neaten the seam and press it.
2. Stitch the sleeve to back part. Neaten the seam and press it.
3. Stitch sleeve edge and side edge with one seam. Neaten seams and press them.

4. Neaten the hem/sleeve hems/neckline edge. Press them into wrong side and topstitch.
5. Neaten plackets all edges. Fold placket's upper edge under and topstitch it. Mark placket's place on front part's wrong side. Stitch the placket to front part. Make a stitch along placket's center; stop stitching at 1.5 cm before placket's lower seam. Pull the coulisse into this hole and gather it.

**TECHNICAL DRAWING:**

