

## Sewing Pattern — Top 5658

Recommendations on fabric: middle/high stretchable jersey (natural or mixed)

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1.5 cm for the hem, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Back part – 1 piece
2. Front part – 1 piece
3. Collar – 1 piece

**NB!** Please make sure that person's head passes through the ring-stitched before you begin sewing.

**OUR ADVICE:** stitch jersey details with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances till 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity

**INSTRUCTIONS:**

1. Stitch side/front/side back edges. Neaten seams and press them backwards.
2. Neaten the hem/armhole edge. Press them into wrong side and topstitch.
3. Stitch the collar as a ring. Press the collar along the center right side out. Stitch outer collar to front/back necklines coinciding notches. Collar seam goes at left shoulder point. Fold collar allowances in and stitch them together.

**TECHNICAL DRAWING:**

