

## Sewing Pattern — Top 5635

Recommendations on fabric: natural/mixed fabric

You will also need: fusing; piping; elastic braid of 0.3 cm in diameter

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 0 cm for armholes, 1 cm for other seams

**Attention!** First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Back part – 1 piece
2. Front part – 1 piece
3. Collar – 2 pieces

Fusing:

1. Collar – 1 piece

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of the collar.
2. Stitch front darts, press them upward.
3. Stitch side edges. Neaten side seams and press them backward.
4. Press the piping along the center and overstretch armholes.
5. Overstretch the collar: begin at the notch, overstretch collar ends and them along upper edge. Turn the collar right side out and press it.

6. Stitch outer collar to the garment. Press the seam toward the collar. Press collar's open edge sidewise and topstitch along the seam.
7. Fold the hem under and sew.
8. Topstitch elastic braid as marked.

**TECHNICAL DRAWING:**

