

## Sewing Pattern — Top 5627

Recommendations on fabric: natural/mixed fabric

You will also need: concealed zip; lining

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

#### Fabric 1:

1. Upper back part – 1 piece
2. Lower back part – 1 piece
3. Upper front part – 2 pieces
4. Lower front part – 1 piece

#### Lining:

1. Upper back part – 1 piece
2. Upper front part – 2 pieces

Our advice: you can use the fabric as the lining.

### **INSTRUCTIONS:**

1. Stitch darts into fabric/lining upper front parts. Press darts toward the center.
2. Lay upper front part on the lining right sides together and overstretch details along middle edge/armholes stopping 1 cm before upper seam. Fold middle edge/armholes allowances into wrong side and overstretch details along upper edge. Turn the details right side out and press them. Make decorative stitch along upper seam at 1 cm from the edge.
3. Stitch fabric upper/lower front parts together. Neaten the seams and press them upward. Neaten lining front part's lower edge.
4. Overstretch upper back part with the lining along upper edge. Turn the details right side out and press them.
5. Stitch fabric upper/lower back parts together. Neaten seams and press them upward. Neaten lining back part's lower edge.
6. Stitch side edges excluding a slit into left side seam. Neaten seams. Press right seam forward, press left seam apart pressing closure slit. Stitch the zipper in. Fix the lining to zipper braid.
7. Topstitch lining lower edge on the seam joining upper/lower parts. Make decorative stitch along middle front sea/armholes/back upper edge at 0.1 cm from the edge.
8. Neaten the hem, fold it under and topstitch at 0.5 cm from the edge.
9. Cut a strap. Fold the strap along the center wrong side out and make a stitch at 0.5 cm from bending. Turn the strap right side out and press it.
10. Pull the strap through front parts as on the sketch.

### **TECHNICAL DRAWING:**

