

## Sewing Pattern — Pants 5608

Recommendations on fabric: fabric with elastic fibers

You will also need: decorative cord; tabs

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 1 cm for all seams, 2 cm for hem allowance

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Side front part – 2 pieces
2. Front part – 2 pieces
3. Back part – 2 pieces
4. Front facing – 2 pieces
5. Back facing – 2 pieces
6. Front sacking – 2 pieces

Fusing: front/back facings, pocket entrance allowance .

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front/back facing and pocket entrance allowance.
2. Overstitch front pocket's upper edge with pocket lining and make decorative stitch. Lay pocket lining on side front part, stitch edges and neat them. Fix side part to front part along upper edge with 3 cm stitch.
3. Stitch side seams and neaten them. Press side seams backwards.

4. Neaten front/middle edges and hems. Stitch inseams and neaten them. Press inseams backwards. Stitch front/middle edges. Make another stitch along crotch seam close to the seam joining front/middle seam.
5. Neaten buttonholes into front upper facing.
6. Stitch side edges of front/back facings, press seams apart. Stitch facings to pants' upper edge and press joining seam towards facings.
7. Neaten lower facings' outer edge. Lay facings on stitches facings right sides together and overstretch upper edge. Topstitch the overstretching on lower facings at 0.2 cm from the seam. Topstitch lower facing's neaten edge on the seam joining upper facing, then press.
8. Press hem allowances into wrong side and topstitch.
9. Pull the cord into buttonholes and set tabs.

**TECHNICAL DRAWING:**

