

Sewing Pattern — Dress 5592

Recommendations on fabric: natural/mixed fabric.

You will also need: concealed zip; fusing

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Back part – 2 pieces
2. Center front part – 1 piece
3. Inner front part – 2 pieces
4. Strap – 1 piece
5. Front skirt – 1 piece
6. Back skirt – 2 pieces

Lining:

1. Back part – 2 pieces
2. Center front part – 1 piece
3. Inner front part – 2 pieces

You can use the fabric as lining.

INSTRUCTIONS:

1. Apply the fusing to wrong side of bodice details.
2. Stitch inner front part to center front part. Neaten the seam and press it toward inner part.
3. Stitch back part to front part. Neaten seams and press them backwards.
4. Do the same for lining details. Neaten lining hem.

5. Fold the strap along the center wrong side out, then make a stitch at 0.5 cm from bending. Turn the strap right side out and press. Sew strap's one edge to front neckline. Fit the dress on, adjust strap's length and sew another end.
6. Stitch skirt side edges. Neaten seams and press them backwards. Stitch back skirt's middle edge between closure notch and the hem. Neaten the seam, press it apart pressing closure slit edges.
7. Stitch the bodice to the skirt. Neaten the seam and press it forward. Stitch the zipper in. Press the seam.
8. Lay the bodice on the lining right sides together. 5 mm before the zipper: fold the lining out and pin it to dress's upper edge. Fold closure allowances into right side and pin them to upper edge (over the facing). Stitch upper edges together. Fold closure allowances into wrong side. Fold the lining upwards and topstitch on the seam allowance at 1-2 mm from the seam. Fold the lining into wrong side and fix it to zipper braid. Press details.
9. Topstitch lining hem along the seam joining the bodice and the skirt.
10. Neaten dress hem, fold it under and topstitch at 1.5 cm from lower edge.

TECHNICAL DRAWING:

