

Sewing Pattern — Dress 5586

Recommendations on fabric: natural/mixed fabric

You will also need: concealed zip for middle seam; piping

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 pieces
2. Front part – 2 pieces
3. First volant – 1 piece
5. Second volant – 1 piece
6. Third volant – 1 piece
7. Forth volant – 1 piece
8. Fifth volant – 1 piece

Lining:

1. Skirt – 1 piece

Our advice: you can do the lining for upper front part.

INSTRUCTIONS:

1. Stitch front/back waist darts. Press front darts towards front center, press back darts towards back center.
2. Stitch bust darts. Slash darts' depths and neaten them. Make soft pleats-darts into front part close to wrapping's edge. Fix dart's ends with stitches at 0.5 cm from side edge.

3. Neaten middle back edge. Stitch middle back seam up to closure notch. Press middle back seam pressing slit edges, then stitch the zipper in.
4. Stitch shoulder edges, neaten them and press backwards.
5. Press the piping along the center and overstitch the neckline and armholes. Fold piping's ends at back part under and fix them by hand.
6. Stitch side edges together: coincide notches and make the wrapping. Neaten side seams and press them backwards.
7. Stitch each volant and skirt lining as a ring. Neaten seams and press them.
8. Fix the third/forth/fifth volants together. Make loose stitch and gather fabric.
9. Stitch the third/forth/fifth volants to skirt lining. Neaten the seam and press it upwards.
10. Fix the first volant/second volant/skirt lining together.
11. Stitch upper front part to the skirt. Neaten the seam and press it upwards.
12. Neaten each volant's lower edge, press lower edges into wrong side and topstitch.

TECHNICAL DRAWING:

