

Sewing Pattern — Dress 5583

Recommendations on fabric: natural/mixing fabric

You will also need: concealed zip; fusing; a button

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 3 cm for upper front part's middle edge, 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Upper back part – 1 piece
2. Lower back part – 1 piece
3. Back yoke – 2 pieces
4. Upper front part – 2 pieces
5. Lower front part – 1 piece
6. Front yoke – 2 pieces
7. Collar – 2 pieces

INSTRUCTIONS:

1. Apply the fusing to wrong side of one front/back yoke, outer collar and middle front seam allowance.
2. Neaten middle front edge and press it by 3 cm.
3. Make loose stitch at 0.5 cm from edge along upper front/back parts' lower/upper edges. Make pleats.
4. Lay front yokes right sides together. Insert upper front part so that front part laid on doubled yoke right sides together (coincide notches!). Stitch details with one seam. Neaten the seam, turn it right side out, then press. Do the same for back yoke and back part.

5. Lay front yoke/lower front part's lower edges together. Stitch together, neaten the seam and press it upward. Make decorative topstitching at 1 mm from the seam. Do the same for the yoke and lower back part.
6. Stitch side seams leaving a segment into left seam unstitched (zipper place). Neaten seams and press them apart, pressing closure slits. Stitch the zipper in.
7. Neaten armholes, fold them under by 0.5 cm, then topstitch. Press seams.
8. Cut a fabric stripe of 3 cm width for the loop. Fold the stripe along the center and topstitch at 0.5 cm from bend overstitching one end. Turn the stripe right side out and press it. Cut the loop of necessary length and tack it to collar's right edge.
9. Lay collars together. Overstitch inner collar with outer one, cut allowances and turn the collar right side out. Press the detail, press lower edges.
10. Stitch the collar to front/back parts coinciding details according to notches.
11. Neaten garment's hem, fold it under and topstitch at 0.5 cm from lower edge.
12. Sew the button to collar's left edge.

TECHNICAL DRAWING:

