

Sewing Pattern — Dress 5581

Recommendations on fabric: natural or mixed fabrics

You will also need: blind zipper of 45 cm long, bias tape.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: armhole and neckline edges– 0cm, all other seams - 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Central back part – 2 details
2. Middle back part – 2 details
3. Side back part – 2 details
4. Central front part – 2 details
5. Middle front part – 2 details
6. Side front part – 2 details

INSTRUCTIONS:

1. Sew princess edges of front and back parts. Leave center seam of back part unsewn. Serge princess seams and press the seam towards center. Press apart center seam of front part.
2. Serge center edge of back part. Sew center seam of back part up to the notches for zipper. Press apart center, press slits for zipper. Sew in zipper.
3. Sew shoulder edges. Serge and press apart shoulder seams.
4. Press bias tape in half lengthwise and overstretch edges of the armhole and neckline.
5. Turn ends of bias tape and tack by hand.
6. Sew side seams of the dress. Serge and press side seams of the dress towards side of back part.
7. Serge lower edge of the dress, turn inside and topstitch by 0, 5 cm off the lower edge.

TECHNICAL DRAWING:

