

Sewing Pattern — Jacket 5567

Recommendations on fabric: natural/mixed fabric

You will also need: fusing; lining; shoulder pads; 4 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 3 cm for garment/sleeve hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Center back part – 2 pieces
2. Side back part – 2 pieces
3. Side front part – 2 pieces
4. Front basque – 4 pieces
5. Back basque – 4 pieces
6. Back neckline facing – 1 piece
7. Center front part – 2 pieces
8. Front band – 2 pieces
9. Collar – 2 pieces
10. Lapel – 4 pieces
11. Upper sleeve – 2 pieces
12. Lower sleeve – 2 pieces

Lining:

1. Back part – 2 pieces
2. Front part – 2 pieces
3. Upper sleeve – 2 pieces
4. Lower sleeve – 2 pieces

Fusing: front band, front part, back neckline facing, collar, lapel

INSTRUCTIONS:

1. Apply the fusing to wrong side of front band, front part, back neckline facing, collar, lapel.
2. Stitch back darts and press them towards back center.
3. Stitch the lapel to the collar, press joining seam apart.
4. Stitch middle back seam and press it apart. Stitch basque's middle seam and press it apart.
5. Stitch front/back relieves and press them apart.
6. Stitch front basque to front part's lower edge. Press joining seam apart.
7. Stitch back basque to back part's lower edge. Press joining seam apart.
8. Stitch side/shoulder edges, press side/shoulder seams apart.
9. Stitch inner collar with lapel into front/back necklines. Press joining seam apart.
10. Stitch shoulder edges of back neckline facing and front bands. Press shoulder seams of facing and front bands apart. Stitch outer collar with lapel into front band/facing neckline. Press joining seam apart.
11. Cut fabric stripe of 3 cm width for loops. Fold the stripe along the center and topstitch at 0.5 cm from bend, overstretching one edge. Turn the stripe right side out and press it. Cut loops and fold them. Tack loops to right front edging.
12. Stitch side edges of front/back parts' basque. Press basque's side seams apart. Neaten basque's upper edge.
13. Pin front band on front part right sides together and overstretch along edging, lapel and collar fall. Lay basques right sides together and overstretch jacket's lower edge, cut corner allowances. Topstitch front edging's overstretching allowance on front band at closure and at front edging at lapels. (Topstitch at 0.2 cm from seam.) Turn edgings right side out. Turn the basque right side out, press the basque and front edgings.
14. Stitch elbow seam and press it apart. Press sleeve hems into wrong side. Stitch sleeve front seam and press it apart.
15. Stitch sleeve into armholes. Sew shoulder pads.
16. Stitch lining details together and stitch sleeve in.
17. Stitch the lining to inner edges of front bands/back neckline facing. Press allowances of seam joining the collar apart and fix them close to seams.
18. Stitch the lining to sleeve hems. Turn the jacket right side out through jacket's bottom. Adjust jacket hem and lining hem. Lay inner basque's upper edge on the lining and topstitch along the seam joining upper basque.
19. Sew buttons on left front edging.

TECHNICAL DRAWING:

