

Sewing Pattern — Jacket 5549

Recommendations on fabric: natural/mixed fabric

You will also need: fusing; lining; shoulder pads; piping; 2 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 pieces
2. Flounce – 3 pieces
3. Flounce facing – 1 piece
4. Front part – 2 pieces
5. Collar – 4 pieces
6. Back neckline facing – 1 piece
7. Center front part – 6 pieces
8. Front band – 2 pieces
9. Upper sleeve – 2 pieces
10. Lower sleeve – 2 pieces
11. Flap – 4 pieces
12. Pocket – 2 pieces

Lining:

1. Back part – 2 pieces
2. Front part – 2 pieces
3. Upper sleeve – 2 pieces
4. Lower sleeve – 2 pieces

Fusing: back neckline facing, outer collar, front band.

INSTRUCTIONS:

1. Apply the fusing to wrong side of back neckline facing, outer collar, front band.
2. Stitch back darts, slash darts' depths, then press them apart.
3. Stitch front darts, slash depths, then press them apart.
4. Lay flaps right sides together, then overstitch. Cut allowances of flap corners, then turn right side out. Press the flap, neaten flap's free edge.
5. Mark pocket's place on front part. Overstitch the pocket along the contour. Press upper edge of patch pocket into wrong side, then topstitch. Press neaten edges into wrong side. Topstitch the pocket in accordance to marking. Mark flap's place. Stitch the flap to marking. Fold the flap downwards and topstitch at 0.5 cm from joining seam.
6. Stitch the collar to center front part, neaten joining seam, then press apart (do this 3 times).
7. Stitch the collar to front band, press joining seam apart.
8. Stitch middle back seam and press it apart.
9. Neaten side edges of flounce/center front part. Stitch seams and press them apart. Stitch side edges if front band/flounce facing and press them apart.
10. Press the piping along the center and overstitch collar's outer edge and center front part.
11. Stitch side/shoulder edges, press side/shoulder seams apart.
12. Lay center front parts together, adjust edges and stitch them to front/back parts. Stitch inner collar into back neckline.
13. Stitch shoulder edges of back neckline facing/front band. Press shoulder edges of facing/front band. Stitch outer collar into facing/front band neckline.
14. Pin front band on front part right sides together and overstitch along edging, fly collar and flounce's lower edge. Cut seams of upper/lower corners of edging. Topstitch edging's overstitching allowance on front band at closure and at front edging at lapels. (Topstitch at 0.2 cm from seam.) Turn edgings right side out.
15. Stitch elbow seam and press it apart. Press sleeve hems into wrong side. Stitch sleeve front seam and press it apart.
16. Stitch sleeve into armholes. Sew shoulder pads.
17. Stitch lining details together and stitch sleeve in, leaving a hole into right front seam of a sleeve and waistband hole into left side seam.
18. Stitch the lining to inner edges of front bands/back neckline facing. Press allowances of seam joining the collar apart and fix them close to seams.

19. Stitch the lining to flounce facing and sleeve hems. Turn the jacket right side out through sleeve hole. Stitch hole's edges together.

20. Make buttonholes into right front part, sew buttons on left one.

TECHNICAL DRAWING:

