

## Sewing Pattern — Jacket 5540

Recommendations on fabric: natural or mixed fabrics

You will also need: fusing; lining; shoulder pads; sleeve heads; 4 buttons; 6 buttons of smaller diameter for vents on sleeve

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm, hem of the garment and of sleeve - 3 cm.

**Attention!** First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. Back part – 2 details
2. Front part – 2 details
3. Collar – 2 details
4. Lapel – 2 details
5. Back neckline facing – 1 detail
6. Front band – 2 details
7. Upper sleeve part – 2 details
8. Lower sleeve part – 2 details

Lining:

1. Back part – 2 details
2. Front part – 2 details
3. Upper sleeve part – 2 details
4. Lower sleeve part – 2 details

Fusing: front band, front part, back part neckline facing, collar, lapel

### **INSTRUCTIONS:**

1. Apply fusing to front band, back neckline facing, front part, collar, lapel.

2. Mark darts on back part. Sew and press darts onto back part towards center. Mark darts on front part. Sew and press darts on front part towards center.
3. Stitch lapel to collar, press connecting seam apart.
4. Sew and press apart center seam of back part.
5. Sew side and shoulder edges of jacket. Press side and shoulder seams apart.
6. Sew lower collar with lapel into the neckline of front / back parts. Press connecting seam apart.
7. Sew shoulder seams of back part neckline facing and front band. Press apart shoulder seams of facing and front band. Sew outer collar with lapel into the neckline of front band and facing. Press connecting seam apart.
8. Lay front band onto right side of front part right side downwards, pin together and overstitch along front band, lapel and outer edge of collar. Stitch lower edges of front bands to front part exactly along marked line of hem turnout. Cut seams of lower corners of front band. Topstitch front band seam allowance: on closure section – onto front band, on lapels section – onto front part band. Stitch by 0,2 cm off the seam. Turn bands onto right side, straighten seams.
9. Sew elbow sleeve seam and vent corners on lower and upper parts of sleeve. Press elbow sleeve seam apart, slash and press the vent. Press hem of sleeve. Sew and press apart front sleeve seam.
10. Sew sleeves into armholes according to notches. Sew in shoulder pads and sleeve heads.
11. Sew seams on details from lining and sew in sleeves, leaving a slit in front right seam of sleeve.
12. Stitch lining to inner edges of front band and of back part neckline facing. Press allowances of collar connecting seams apart and fix close to seams.
13. Stitch lining to hem of jacket and hem of sleeve. Turn jacket through the slit in sleeve. Sew the slit in sleeve.
14. Serge buttonholes on right front part, sew buttons on left front part. Mark and sew buttons on sleeve.

### **TECHNICAL DRAWING:**

