

Sewing Pattern — Jacket with Decorative Topstitching 5536

Recommendations on fabric: denim.

You will also need: fusing; 1 button; lining; shoulder pads.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 3 cm for garment/sleeve hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Side front part – 2 pieces
2. Middle front part – 2 pieces
3. Center front part – 2 pieces
4. Center front part_2 – 2 pieces
5. Front insert – 2 pieces
6. Front yoke – 2 pieces
7. Back part – 2 pieces
8. Side back part – 2 pieces
9. Inner collar – 1 piece
10. Outer collar – 1 piece
11. Back neckline facing – 1 piece
12. Front band – 2 pieces
13. Upper sleeve – 2 pieces
14. Lower sleeve – 2 pieces

Lining:

1. Side front part – 2 pieces
2. Middle front part – 2 pieces
3. Center front part – 2 pieces
4. Center front part_2 – 2 pieces
5. Front insert – 2 pieces

6. Front yoke – 2 pieces
7. Back part – 2 pieces
8. Side back part – 2 pieces
9. Upper sleeve – 2 pieces
10. Lower sleeve – 2 pieces

Fusing: front band, front yoke, center front part, jacket/sleeve hems, back neckline facing, outer collar.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front band, front yoke, center front part, jacket/sleeve hems, back neckline facing, outer collar.
2. Stitch back darts and press them towards the center.
3. Lay outer collar in inner one and overstretch them. Press the collar.
4. Stitch side front part to middle front part. Press joining seam apart and make decorative stitch at 0.5 cm from joining seam. Stitch the insert to center/side front parts. Press joining seam apart and make decorative stitch at 0.5 cm from joining seam.
5. Stitch center front part_1 and center front part_2 together. Press front part's seam and make decorative stitch at 0.5 cm from seam.
6. Stitch middle front part to center front part. Press joining seam and make decorative stitch at 0.5 cm from seam.
7. Stitch front yoke to lower front part. Press joining seam apart and make decorative stitch at 0.5 cm from joining seam.
8. Pin front band on front part right sides together and overstretch along edging. (Overstretch front part upward the notch determining end of stitching the collar in). Stitch lower edges of front bands to front part along marked hem line. Cut seams of upper/lower corners of edging. Topstitch edging's overstretching allowance on front band at closure and at front edging at lapels. (Topstitch at 0.2 cm from seam.) Turn edgings right side out.
9. Stitch middle back seam and press it apart. Stitch relieve back seams and press them apart. Stitch shoulder/side seams, then press seams apart.
10. Stitch shoulder edges of back neckline facing/front band, then press seams apart. Stitch inner collar into jacket neckline, stitch outer collar into edges of back neckline facing/front band.
11. Stitch elbow seams and press it apart. Press sleeve hems into wrong side. Stitch sleeve front seams and press them apart.
12. Stitch sleeve into armholes according to notches. Sew shoulder pads.
13. Stitch lining details together and stitch sleeve in, leaving a hole into right front seam of a sleeve and waistband hole into left side seam.
14. Stitch the lining to inner edges of front bands/back neckline facing. Press allowances of seam joining the collar apart and fix them close to seams.
15. Stitch the lining to jacket/sleeve hems. Turn the jacket right side out through sleeve hole. Stitch hole's edges together.
16. Make a buttonhole into right front edging, sew the button on left one.

TECHNICAL DRAWING:

