

Sewing Pattern — Wrapped Jacket 5535

Recommendations on fabric: natural/mixed fabric.

You will also need: fusing; lining; shoulder pads.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 3 cm for garment/sleeve hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 2 pieces
2. Side back part – 2 pieces
3. Front yoke – 2 pieces
4. Upper front part – 2 pieces
5. Middle front part – 2 pieces
6. Lower front part – 2 pieces
7. Front band – 2 pieces
8. Waistband_1 – 2 pieces
9. Waistband_2 – 2 pieces
10. Upper sleeve – 2 pieces
11. Lower sleeve – 2 pieces
12. Inner collar – 1 piece
13. Outer collar – 1 piece
14. Back neckline facing – 1 piece

Lining:

1. Back part – 2 pieces
2. Side back part – 2 pieces
3. Front yoke – 2 pieces
4. Lower front part – 2 pieces
5. Upper sleeve – 2 pieces

6. Lower sleeve – 2 pieces

Fusing: front band, front yoke, upper/middle/lower front parts, jacket/sleeve hems, back neckline facing, outer collar.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front band, front yoke, upper/middle/lower front parts, jacket/sleeve hems, back neckline facing, outer collar.
2. Stitch back darts and press them towards the center.
3. Lay outer collar on the inner one, then overstitch. Press the collar.
4. Stitch upper front part to front yoke, press joining seam apart. Stitch front middle part to upper front part, press joining seam apart. Stitch lower front part to middle front part, press joining seam apart.
5. Lay waistband_1 details right sides together and overstitch along three edges excluding side edge. Turn the waistband right side out and press it. Process waistband_2 in the same way. Stitch the waistband to edging (stitch longer waistband to left edging, stitch shorter waistband to right one.)
6. Pin front band on front part right sides together and overstitch along edging. (Overstitch front part upward the notch determining end of stitching the collar in). Stitch lower edges of front bands to front part along marked hem line. Cut seams of upper/lower corners of edging. Topstitch edging's overstitching allowance on front band at closure and at front edging at lapels. (Topstitch at 0.2 cm from seam.) Turn edgings right side out.
7. Stitch middle back seam and press it apart. Stitch relieve back seams and press them apart. Stitch shoulder/side seams leaving waist-level hole into right side seam for the waistband, then press seams apart.
8. Stitch shoulder edges of back neckline facing/front band, then press seams apart. Stitch inner collar into jacket neckline, stitch outer collar into edges of back neckline facing/front band.
9. Stitch elbow seams and press it apart. Press sleeve hems into wrong side. Stitch sleeve front seams and press them apart.
10. Stitch sleeve into armholes according to notches. Sew shoulder pads.
11. Stitch lining details together and stitch sleeve in, leaving a hole into right front seam of a sleeve and waistband hole into left side seam.
12. Stitch the lining to inner edges of front bands/back neckline facing. Press allowances of seam joining the collar apart and fix them close to seams. Fix the lining to the fabric at waistband-hole level.
13. Stitch the lining to jacket/sleeve hems. Turn the jacket right side out through sleeve hole. Stitch hole's edges together.

TECHNICAL DRAWING:

