

Sewing Pattern — Double-Layer Dress 5527

Recommendations on fabric: natural/mixed fabric.

You will also need: chiffon for outer layer, zipper of 25 cm.

If the pattern has double contour the seam allowances are included. Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for fabric garment hem.

<u>Attention</u>! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

- 1. Right center front part 1 piece
- 2. Left center front part 1 piece
- 3. Right side back part 1 piece
- 4. Left side back part 1 piece
- 5. Right side front part 1 piece
- 6. Left side front part 1 piece
- 7. Upper center front part 1 piece

Chiffon:

- 1. Center back part 2 pieces
- 2. Side back part 2 pieces
- 3. Side front part 2 pieces
- 4. Center front part 1 piece

INSTRUCTIONS:

1. Lay outer layer's pieces on the dress right sides together. Stitch relieve seams into front/back outer layers. Neaten relieve seams and press front seams towards front center, press back seams towards back center.

2. Stitch side seams of outer layer, neaten them and press them backwards.

3. Lay dress inner details right sides together. Stitch relieve edges of inner front/back layers. Neaten



relieve seams and press front seams towards front center, press back seams towards back center.

4. Stitch inner dress side seams, neaten them and press backwards.

5. Neaten outer dress hem, press it under and topstitch. Neaten the edge of inner dress, fold it under and topstitch at 1.5 cm distance.

6. Neaten middle edge of outer/inner dresses, stitch up to closure notch. Press middle seam of outer/inner dresses, press closure slit. Stitch the zipper into middle seam of outer dress.

7. Cut straps. Fold straps along the center and make a stitch at 0.5 cm from bending. Turn straps right side out and press them. Sew straps to front décolleté edge.

8. Lay outer dress right side on inner dress wrong side and overstitch décolleté edge of front/back parts. Topstitch overstitching allowance on inner dress qt 0.2 cm from overstitching.

9. Put the dress on, adjust straps and sew back ends to back part. Adjust middle edges of outer dress and inner dress and fix them ar closure segment.

TECHNICAL DRAWING:

