

## Sewing Pattern — Waistcoat 5499

Recommendations on fabric: moreen or viscose.

You will also need: fusing; lining; separable zipper.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 3 cm for hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Center back part – 1 piece
2. Pocket – 2 pieces
3. Center front part – 2 pieces
4. Collar – 2 pieces
5. Front band – 2 pieces
6. Lower back facing – 1 piece
7. Lower front facing – 2 pieces

#### Lining:

1. Center back part – 1 piece
2. Center front part – 2 pieces

Fusing: front band, outer collar.

## **INSTRUCTIONS:**

1. Apply the fusing to front band, outer collar.
2. Stitch front darts and press them downwards. Stitch back darts and press them towards back center.
3. Neaten pocket outer contour and press it according to pattern. Topstitch upper edge on the pocket, mark pocket place and topstitch the pocket along the contour at 0.2 cm from pocket edge.
4. Stitch side/shoulder edges and press them apart.
5. Lay collar details together and overstretch the collar along the contour. Turn collar corners right side out. Press the collar.
6. Stitch the zipper under edging. Fold edging under and press it (at closure segment).
7. Stitch side edges of front/back hem facings. Lay hem facings on the garment right sides together and overstretch the hem. Topstitch hem overstretching allowance on facings at 0.2 cm from seam; stop stitching 5 cm before edging.
8. Pin front band on front part right sides together. Stitch front band lower edge to front part facing's upper edge; stop stitching 1 cm before front band edge. Overstretch edgings with front bands along edging lines (at front part side). Cut extra fabric of edging's seams lower corners. Turn edgings right side out and press seams.
9. Stitch the collar into waistcoat neckline. Make decorative stitch at 0.5 cm along edging line.
10. Stitch lining details leaving a hole into right side seam. Press the lining.
11. Stitch the lining to front bands and hem facing and outer collar coinciding with garment seams. Press allowance of seam joining the collar apart and fix them close to seams. Stitch lining side seam.

## **TECHNICAL DRAWING:**

