

Sewing Pattern — Blouse 5495

Recommendations on fabric: fabric suitable for blouse.

You will also need: fusing, 10 buttons.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for garment hem.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 piece
2. Front part – 2 pieces
3. Collar – 2 pieces
4. Stand-up collar – 2 pieces
5. Cuff – 2 pieces
6. Sleeve – 2 pieces
7. Front band – 2 piece

Fusing: front band, outer collar, stand-up collar, cuff.

INSTRUCTIONS:

1. Apply the fusing to wrong side of front band, outer collar, stand-up collar, cuff.
2. Stitch front darts. Stitch back darts. Stitch back waist darts. Press darts towards the center.
3. Neaten front band inner edge.
4. Overstitch edgings with front bands, slash extra fabric in corners and turn front bands right sides out. Press edgings.
5. Stitch shoulder/side edges. Neaten shoulder/side seams and press them backwards. Fix front bands with 1 cm stitch at shoulder seams.
6. Neaten sleeve edges. Stitch sleeve seam to the notch, press the seam apart. Press the slit and make

decorative stitch at 0.5 cm distance.

7. Stitch sleeves in.

8. Overstitch inner collar with outer one; turn the collar right side out. Press the collar.

9. Stitch stand-ups inserting the collar between them. Press stand-up collar.

10. Stitch inner stand-up with collar into neckline, fold outer stand-up open edge under and topstitch along the seam joining inner stand-up.

11. Neaten cuff's side edges and turn the cuff right side out. Press ready cuff.

12. Stitch outer cuff to sleeve lower edge. Fold inner cuff under and topstitch it. Make buttonholes into the cuff. Sew buttons.

13. Neaten garment hem, fold it under and topstitch.

14. Make buttonholes into right front part, sew buttons on left one.

TECHNICAL DRAWING:

