

## Sewing Pattern — Denim Jacket with Shaped Yoke 5489

Recommendations on fabric: denim.

You will also need: fusing, separable zipper, 2 studs.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Front yoke – 2 pieces
2. Insert – 2 pieces
3. Center front part – 2 pieces
4. Side front part – 2 pieces
5. Front waistband – 2 pieces
6. Back yoke – 1 piece
7. Back insert – 2 pieces
8. Side back part – 2 pieces
9. Center back part – 2 pieces
10. Back waistband – 2 pieces
11. Stand-up collar – 2 pieces
12. Front band – 2 pieces
13. Lower front waistband – 2 pieces
14. Upper sleeve – 2 pieces
15. Lower sleeve – 2 pieces
16. Sleeve cuff – 4 pieces

Fusing: front band, stand-up collar, cuff, back waistband and lower waistband.

---

## **INSTRUCTIONS:**

1. Apply the waistband to wrong side of front band, stand-up, cuff, back waistband and lower waistband.
2. Fold stand-up details along the center, wrong side out, and overstitch along outer contour to notch. Slash corners and turn right side out. Press stand-up collar.
3. Sew side part to center front part. Neaten the seam and press it towards front center. Sew the insert to front part. Neaten the seam and press it towards insert. Make decorative stitch at 0.5 cm from seam joining side front part and insert.
4. Sew side back part to center back part. Neaten joining seam and press it towards back center. Sew back figure insert to back part. Neaten joining seam and press towards insert. Make decorative stitch at 0.5 cm from seam joining side back part and figure insert.
5. Sew front yoke to front part, neaten joining seam and press it towards front part. Make decorative stitch at 0.5 cm from seam joining yoke.
6. Sew middle back edge. Neaten joining seam and press it towards right back part. Make decorative stitch at 0.5 cm from joining seam.
7. Sew back yoke to back part. Neaten joining seam and press it towards front part. Make decorative stitch at 0.5 cm from seam joining front part.
8. Sew waistband to front part and press joining seam towards waistband. Sew waistband to back part and press joining seam towards waistband.
9. Sew front/back lower waistband side edges and press them apart. Neaten waistband upper edge.
10. Fold front parts right sides together, coincide yokes and measure edgings lengths. Sew the zipper to edging. Fold edge at zipper segment and press it.
11. Neaten front band outer edge. Lay front band on front part right sides together and overstitch along edging line (topstitch at front part side). Turn edgings right side out and press.
12. Sew shoulder/side seams and press them apart. Press shoulder/side seams backwards.
13. Sew outer stand-up collar into neckline, fold inner stand-up open edge and topstitch it along seam joining outer stand-up. Make decorative stitch along stand-up collar. Fix front bands at shoulder seams with 1 cm stitch.
14. Sew lower waistband middle edge to front band outer edge, at bottom. Press joining seam and turn it right side out. Overstitch edging lower corner and garment hem with waistband. Slash edging lower corners and turn them right side out. Press the waistband, making edging of upper waistband, and topstitch upper neaten edge on seam joining waistband. Make decorative stitch along the zipper at 0.5 cm from edging.
15. Neaten sleeve elbow edge. Stitch sleeve elbow seam to notch. Press elbow seam apart and topstitch slit allowance at 0.5 cm on the sleeve. Make decorative stitch at 0.5 cm from elbow seam. Stitch sleeve front seam and neaten it.
16. Fold cuffs right sides together and overstitch along outer contour. Sew outer cuff to sleeve lower edge. Fold inner cuff upper edge at 1 cm and topstitch along seam joining outer cuff. Make decorative stitch along cuff contour. Stitch sleeves into armholes according to notches. Make studs into stand-up collar.

**TECHNICAL DRAWING:**

