

Sewing Pattern — Jacket 5483

Recommendations on fabric: suedette.

You will also need: 4 separable zippers

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 2 cm for garment/sleeves hems

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back sleeve – 2 pieces
2. Front sleeve – 2 pieces
3. Center back part – 1 piece
4. Side back part – 2 pieces
5. Side front part – 2 pieces
6. Center front part – 2 pieces

INSTRUCTIONS:

1. Sew back relieves and press them apart.
2. Sew the zipper to sleeve upper edge. Press joining seams. Fold sleeve hem under and press it. Make decorative stitch at 0.5 cm along zipper catching garment hem. Sew sleeve lower edge and press apart. Topstitch sleeve hem.
3. Sew the zipper to side/center front part allowances. Press joining seam. Mark center front part edge under. Topstitch garmenthem.
4. Sew jacket side edges and press them apart. Sew sleeves into armholes. Press garment hem under and topstitch. Make decorative stitch at 0.5 cm along zipper.

5. Make decorative stitch at 0.2 cm from front/back neckline edge.

TECHNICAL DRAWING:

